



# Vandal Resistant Barrier-Free Versacooler®



Distribuidor:  
Novo Agua SA de CV  
Tel: (0181)8129-5307  
Tel y fax: 8311-8352

## PV8AM

### Suggested Specification

Model PV8AM shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water. Model PV8AM shall include a single **vandal resistant** push button to activate the flow of water. Basin shall be designed to eliminate splashing and standing water. Bubbler shall be of one-piece stainless steel construction, **vandal resistant**, and operate between 20 and 120 psi. Cabinet finish shall be brushed stainless steel. All cabinet fasteners shall be **vandal resistant**. Cabinet shall have perforated galvanized steel screen to prevent objects from being inserted into the cooler. Cooling system shall use R-134a refrigerant. Shall comply with ANSI A117.1 and ADA. Shall be listed by Underwriters Laboratories, certified to the Air Conditioning and Refrigeration Institute Standard 1010, certified by Canadian Standards Association and conform to European Union Directives. Shall comply with ANSI/NSF 61.

### Model

**PV8AM** Delivers 8.0 gallons of chilled drinking water per hour. This model satisfies CABO/ANSI A117.1 and when properly installed, allows your facility to comply with ADA requirements.

### Standard Features

- Built in 100 micron strainer stops particles before they enter the waterway
- Waterways are lead-free in materials and construction
- Stainless steel top
- Brushed stainless steel finish
- One-piece **vandal resistant** stainless steel bubbler
- Galvanized steel louver and bottom screen
- Heavy duty galvanized steel mounting frame
- High efficiency cooling tank and coil
- Refrigerant R-134a
- **Vandal resistant** front push button
- **Vandal resistant** fasteners

### Finishes

- Standard Cabinet Finish: Brushed Stainless Steel

### Installation

- Prior to roughing-in, consult local, state, and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide access for installation



### ADA Compliant



Components in this fountain are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.

**Limited 5-Year Warranty** (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample copy available upon request.

**Export Warranty:** One-year on sealed refrigeration system and most component parts. Four-year replacement contract on sealed refrigeration system. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Model covered by this specification comply with all known Plumbing Codes. Listed by Underwriters' Laboratories. Certified by Canadian Standards Association, and Certified to Air Conditioning and Refrigeration Institute Standard 1010.



Model	50°F Drinking Water 90°F Ambient Air Temperature*			115 Volts, 60 HZ		Glass Filler Acc. Option	Net Wt. Approx.
	Rated Capacity GPH	Base Rate GPH	Pre-Cooler	Full Load Amps	Rated Watts		
PV8AM	8.0	8.0	No	4.8	380	No	56 Lbs.

\*Air Conditioning and Refrigeration Institute Standard Rating Condition 80°F inlet water temperature.

